



- OIML R76:2006 Approved in Compliance with EN45501:2015 and NAWI directive 2014/31/EU
- High Speed 24 bits Multiplexed Delta-Sigma A/D Converters for Fast and Stable Weighing
- Dual Weighing Range
- Simple Piece Counting, HI-OK-LO Indicator and Alarm
- Easy Grip Design for Mobility Convenience
- Wide Angle LCD Display with LED Backlight
- Pan Size: 225 x 320mm with Stainless Steel Insert

- OIML R76:2006 Approved in Compliance with EN45501:2015 and NAWI directive 2014/31/EU
- High Speed 24 bits Multiplexed Delta-Sigma A/D Converters for Performance and Stability
- Dual Weighing Range
- Simple Piece Counting, HI-OK-LO Indicator and Alarm
- Wide Angle LCD Display with LED Backlight
- Compact Design for Space Efficiency
- Overload and Shock Protection Mechanism Protects against Excessive Loads and Shock
- Easy Grip Design for Mobility Convenience
- Functions Including: Power On Zero Tracking, Manual Zero, Dual Weighing Range, Full Subtractive Tare, Memory Accumulation, kg/lb Conversion, Simple Piece Counting, HI-OK-LO Indicator and Alarm, Auto Power Saving, Low Battery Warning and Charging Status Indicator
- Features Including: Backlight, Platter with SUS304 Insert, Rechargeable Battery, Power Adaptor, Adjustable Feet
- Long Battery Operation Time: 200 Hours Plus

Model	VOW-3	VOW-6	VOW-15	VOW-30
Capacity (W1/W2)	1.5 / 3 kg	3 / 6 kg	6 / 15 kg	15 / 30 kg
Readability (e1/e2)	0.5 / 1 g	1 / 2 g	2 / 5 g	5 / 10 g
Maximum Display Resolution	60,000d	60,000d	75,000d	60,000d
Weighing Units	kg, g, lb, oz			
Tare Range	T= -Max(SUBTRACTIVE)			
Display	6 Digits of 33mm in Height			
Pan Size (W × L)	225 x 320mm with Stainless Steel Insert			
Operating Environment	-10°C ~ 40°C (14 o ~104 o F), Non-condensed. R.H. ≤85%			
Power Source	By Built-in 6V4Ah Rechargeable Battery or Power Adaptor			
Battery Life	200 Hours Plus			
Options Available	4 Channels Relay Output Interface, RS232 Interface, Real Time Clock, SUS304 Platter cover			
Scale Dimensions (W × L × H)	307x320x120mm			



UNIVERSAL WEIGHT ELECTRONICS CO., LTD.

4th FLOOR, NO.53, BAOXING ROAD, XINDIAN DISTRICT, NEW TAIPEI CITY 231, TAIWAN (R.O.C)

Tel: +886-2-29180121 (12Lines) Fax: +886-2-29181508

<http://www.uwe.com.tw> e-mail : int@uwe.com.tw