



BMI

SERIES

THE BODY MASS INDEX SCALE





FEATURES

- OIML-R76 and EC Class III Type Approved
- Heavy Duty Mold Injected Aluminum Alloy Platform
- Stainless Steel Platform Cover
- Overload Protection Devices Against Excessive Load or Shock Applied
- Equipped with Complete Numeric Keypad, EMI Calculation, Ideal Weight Calculation, Height Estimation, Auto Data Saving, Data Recall and Auto Power Saving
- 5-3-2 x 22mm Wide Angle LCD Display Digits for WEIGHT-HEIGHT-EMI Display
- Detachable Indicator able for Wall Mounting
- Dual Power Source: By Built-in Rechargeable Battery or Power Adaptor
- Long Battery Operating Time: 150 Hours Plus
- Non-slip Foot Pad, Bubble Level, Adjustable Feet, Rechargeable Battery and Power Adaptor Included

OPTION AVAILABLE

- EL Backlight
- Printer Interface
- RS232C Interface

SPECIFICATIONS

Model No.	Max ₁ (kg)	e ₁ (kg)	Max ₂ (kg)	e ₂ (kg)	Platform
BMI-2-30	30kg x 10g single interval				330 x 450mm with Stainless Steel Cover
BMI-2-200	150	0.05	200	0.1	
BMI-3-250	150	0.05	250	0.1	420 x 520mm with Stainless Steel Cover
Tare Range	Full Range (Subtractive)				
Power Source	By Built-in Rechargeable Battery or External AC/DC Power Adaptor				
Operating Environment	0° ~ 40°C (32° ~ 104°F), Non-condensed. R.H. ≤ 85%				

* Specifications subject to change without notice



unit = mm



UNIVERSAL WEIGHT ENTERPRISE CO., LTD.

2-5 Floor No. 39 Pao Shing Road Hsin Tien City 231 Taipei Hsin Taiwan R.O.C.
Tel : +886-2-29180121 (12 Lines) Fax : +886-2-29181508-29183052-29112176-7
<http://www.uwe-scale.com.tw> e-mail: uwe@ms39.hinet.net

May 2003 Designed by DAILY
Printed in Taiwan