



DM SERIES

The *Deltaweigher*





FEATURES

- Two Display Accuracy Versions for Various Applications
- 5 x 24mm LCD Display Digits
- Dual (Metric and Avoirdupois) Weight Units
- Tact-Switch Keyboard
- Cockroach Resistance Design
- Overload and Shock Protection Mechanism
- Dual Power Source
- 120 Hours Battery Operating Time
- Low Battery Indicator
- Battery Charge Status Indicator
- Auto Power Off Function
- Auto Calibration
- Manual Zero Function
- Initial Zero Tracking Function
- All Stainless Steel Platter Cover Included
- External Power Adaptor Included
- Bubble Level Included
- Adjustable Feet Included

OPTIONS AVAILABLE

- Rear Display
- Backlight
- RS232C Interface Output

SPECIFICATIONS

Model No.	Capacity	Division	Accuracy	Min.
DM-3000	3000g	1g	1/3000	20g
DM-6000	6000g	2g	1/3000	40g
DM-15K	15kg	0.005kg	1/3000	0.1kg
DM-30K	30kg	0.01kg	1/3000	0.2kg
DM-1100	1100g	0.1g	1/11000	2g
DM-11K	11kg	1g	1/11000	20g
Tare Rang	Full Tare Range (Subtractive)			
Platter	215 x 250mm with All Stainless Steel Platter Cover			
Display Type	5 x 24mm LCD Digits			
Power source	By Built-in Rechargeable Battery or Power Adaptor			
Operation Environment	0°-40°C (32°-104°F), Non-condensed. R.H. ≤ 85%			
Standard Package	Individually Packed 370 x 365 x 255mm Net/Gross Weight: 3.7/5.0kg			

Specifications subject to change without notice



unit = mm



UNIVERSAL WEIGHT ENTERPRISE CO., LTD.

2-5 Floor No. 39 Pao Shing Road Hsin Tien City 231 Taipei Hsien Taiwan R.O.C.
Tel : +886-2-29180121 (12 Lines) Fax : +886-2-29181508 29183652 29112176-7
<http://www-scale.com.tw> e-mail: uwe@ms8.hinet.net

Oct '2001 Designed by DAILY
Printed in Taiwan