



# PACO SERIES



THE BENCH & FLOOR SCALE





# PACO

## FEATURES

- Heavy Duty & Well Finished Steel Structure Platform
- Stainless Steel Platform Cover
- Overload Protection Devices Against Excessive Load or Shock Applied
- Equipped with Auto Calibration, Auto Zero Tracking, Full Tare Range and Auto Power Saving
- 5 x 24mm Wide Angle LCD Display Digits
- Detachable Indicator Able to Wall Mounting
- Indicator Able to Table Standing (with optional table stand kit)
- Dual Power Sources: By Built-in Rechargeable Battery or Power Adaptor
- Complete with Low Battery and Charging Status Indicator
- Long Battery Operating Time: 150 Hours Plus
- Odd Weight Calibration Available for Capacity Over 150kg
- Bubble Level, Adjustable Feet, EL Backlight Included



## OPTIONS AVAILABLE

- Table Stand kit
- RS232C Interface

## SPECIFICATIONS

Model No.	Capacity (kg)	Division (kg)	Platform	Individual Package
PD-B30	30	0.005	330 x 450mm with Stainless Steel Cover	80(L)x50(W)x22(H)cm Net/Gross Weight:14/16kg
PD-B75	75	0.01		
PD-B150	150	0.02		
PD-F75	75	0.01	420 x 520mm with Stainless Steel Cover	88(L)x64(W)x22(H)cm Net/Gross Weight:19/21kg
PD-F150	150	0.02		
PD-F300	300	0.05		
PD-L150	150	0.02	500 x 600mm with Stainless Steel Cover	88(L)x64(W)x22(H)cm Net/Gross Weight:28/31kg
PD-L300	300	0.05		
PD-L600	600	0.1		
PD-XL150	150	0.02	600 x 800mm with Stainless Steel Cover	110(L)x73(W)x26(H)cm Net/Gross Weight:42/58kg
PD-XL300	300	0.05		
PD-XL600	600	0.1		
Tare Range	Full Range (Subtractive)			
Power Source	By Built-in Rechargeable Battery or AC/DC Power Adaptor			
Operating Environment	0° ~ 40°C (32° ~ 104 °F) Non-Condensed. R.H. ≤ 85%			

• Specifications subject to change without notice



## UNIVERSAL WEIGHT ENTERPRISE CO., LTD.

2-5 Floor No. 39 Pao Shing Road Hsin Tien City 231 Taipei Hsien Taiwan R.O.C.  
Tel : +886-2-29180121 (12 Lines) Fax : +886-2-29181508 · 29183652 · 29112176-7  
http://www.uwe.com.tw e-mail:uwe@ms8.hinet.net

Feb 2004 Designed by DAILY  
Printed in Taiwan